

Amendments to the Claims:

This listing of claims shall replace all prior versions, and listings, of claims in the application.

Listing of Claims

Claims 1-9 (Canceled)

10. (New) An optical reader comprising:
a lens system for focusing, along an optical path, an image of an object being read;
an image sensor array disposed in the optical path for detecting a signal representative of the image, wherein the image sensor array is disposed at a tilt angle α with respect to the optical path of lens system;
means for rotating the image on the image sensor array about a rotational axis defined along the optical path while maintaining the tilt angle α .

11. (New) An optical reader according to Claim 10, wherein the means for rotating the image of the object comprises means for synchronizing rotation of the image with a timing cycle of raster scan line reading of the image sensor array.

12. (New) An optical reader according to Claim 10, wherein the means for rotating the image comprises a dove prism.

13. (New) An optical reader according to Claim 10, wherein the means for rotating the image comprises a mirror assembly.

14. (New) An optical reader according to Claim 10 wherein the image sensor array comprises a two-dimensional array.

15. (New) An optical reader comprising:
a lens system for focusing along an optical path an image of an object being read;
a plurality of image sensor arrays disposed in the optical path for detecting a signal representative of light reflected from the object through said lens system, wherein each of said image sensor arrays is disposed at approximately a same tilt angle α with respect to the optical path, wherein each of said image sensor arrays being oriented at a different rotational angle to the optical path in relation to one another.

16. (New) An optical reader according to Claim 15 wherein said plurality of image sensor arrays comprises first and second image sensor arrays.

17. (New) An optical reader according to Claim 16 wherein said first and second image sensor arrays are oriented at a different rotational angle to the optical path, spaced by about 90 degrees to one another.

18. (New) An optical reader according to Claim 15 wherein said plurality of image sensor arrays comprises first, second and third image sensor arrays.

19. (New) An optical reader according to Claim 18 wherein said first, second and third image sensor arrays are oriented at a different rotational angle to the optical path, evenly rotationally spaced about the optical path.

20. (New) A method of optical reading comprising the steps of:

 focusing, along an optical path, an image of an object being read onto an image sensor array;

 detecting, at the image sensor array, a signal representative of the image, the image sensor array being disposed at a tilt angle α with respect to the optical path;

 rotating the image of the object about a rotational axis defined along the optical path while maintaining the tilt angle α .